

Parce	el Base	/ Source	Date: N/A	
Rev. No.:	Rev. By:	Rev. Date:	Description:	
1	RRH	8-31-10	Fixed note from "GROOVE AND TONGUE" to "TONGUE AND GROOVE"	

CONE SECTION WITH MODIFIED TONGUE—AND GROOVE JOINTS AND WITH STUD INSERTS CAST IN PLACE. TOP TO HAVE

TRANSITION SECTION MUST BE-

FIRST SECTION BELOW CONE.

PVC. SCHEDULE 40 -

OR STEPS AND CONE

POSITIONED.

BETWEEN BRACKETS 10'

SECTION SHALL BE RE-

LOCATION SHALL NOT INTER-

FERE WITH MANHOLE STEPS,

MINIMUM TWO DURAN INC. RELINER STAINLESS STEEL ADJUSTABLE CLAMPING

PVC OR ABS PLASTIC DROP PIPE SHALL BE ONE PIPE SIZE SMALLER

(6" MIN.) THAN PIPE ENTERING

MANHOLÉ. LOCATION SHALL BE

FLUSH WITH MANHOLE WALL AND

1/4" TO 1-1/2" ANGULAR GRADED-STONE OR CAREFULLY AND UNIFORMLY TAMPED SAND IN MAXIMUM 6" LAYERS.

NOT INTERFERE WITH MANHOLE STEPS.

BRACKETS ATTACHED TO MANHOLE WALL

WEDGE ANCHORS, STAINLESS STEEL WASHERS AND NUTS. MAXIMUM SPACING

WITH TWO (EACH) 3/8" STAINLESS STEEL

PLASTIC DROP PIPE.

FINISH SURFACE.



INTERIOR DROP CONNECTION

ONE PUBLIC WORKS DRIVE, BLDG 95 WE WATERFORD, MICHIGAN 48328-1907

ST	ORIG. DATE:	06/18/03	SHEET:
	SCALE:	NONE	1 of 1